

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

L19009 - UV-A1 Primer

Product no.

L19009

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

UV filling insulating base for autobody application

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

HBC System Smarttool Production ApS

Hobrovej 961-963

9530 Støvring

Denmark

tel:+45 70 22 70 70

Contact person

Vibeke Jørgensen

E-mail

info@hbc-system.com

SDS date

2016-05-27

SDS Version

2.0

1.4. Emergency telephone number

Use your national or local emergency number

See section 4 "First aid measures"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

STOT RE 1; H372

Skin Sens. 1; H317

Repr. 2; H361

Asp. Tox. 1; H304

Eye Irrit. 2; H319

Skin Irrit. 2; H315

Aquatic Chronic 3; H412

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

- Causes damage to organs through prolonged or repeated exposure. (H372)
- May cause an allergic skin reaction. (H317)
- Suspected of damaging fertility or the unborn child. (H361)
- May be fatal if swallowed and enters airways. (H304)
- Causes serious eye irritation. (H319)
- Causes skin irritation. (H315)
- Harmful to aquatic life with long lasting effects. (H412)

Safety statement(s)	General	-
	Prevention	Obtain special instructions before use. (P201). Do not breathe vapours. (P260).
	Response	Wear protective gloves/protective clothing/eye protection. (P280). Get medical advice/attention if you feel unwell. (P314). IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310). IF exposed or concerned: Get medical advice/attention. (P308+P313).
	Storage	-
	Disposal	-

Identity of the substances primarily responsible for the major health hazards

styrene , hexamethylene diacrylate hexane-1,6-diol diacrylate , PHENYL,BIS,2,4,6-TRIMETHYLBENZOYL,-PHOSPHINE,OXIDE

2.3. Other hazards

This product contains substances that can give chemical pneumonia if inhaled. The symptoms of chemical pneumonia can appear after several hours.
This product contains an organic solvent. Repeated exposure to organic solvents can result in damage to the nervous system and inner organs, such as the liver and kidneys.

Additional labelling

-

Additional warnings

-

VOC

VOC-MAX: 285 g/l, MAXIMUM VOC CONTENT (B/c1): 540 g/l.

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME:	styrene
IDENTIFICATION NOS.:	CAS-no: 100-42-5 EC-no: 202-851-5 REACH-no: 012119457861-32 Index-no: 601-026-00-0
CONTENT:	15-25%
CLP CLASSIFICATION:	Flam. Liq. 3, Acute Tox. 4, STOT RE 1, STOT SE 3, Skin Irrit. 2, Eye Irrit. 2, Asp. Tox. 1, Aquatic Chronic 3
NOTE:	H226, H304, H315, H319, H332, H335, H372, H412 S
NAME:	hexamethylene diacrylate hexane-1,6-diol diacrylate
IDENTIFICATION NOS.:	CAS-no: 13048-33-4 EC-no: 235-921-9 REACH-no: 01-2119484737-22 Index-no: 607-109-00-8
CONTENT:	10-15%
CLP CLASSIFICATION:	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3 H315, H317, H319, H412
NAME:	acetone propan-2-one propanone
IDENTIFICATION NOS.:	CAS-no: 67-64-1 EC-no: 200-662-2 REACH-no: 01-2119471330-49 Index-no: 606-001-00-8
CONTENT:	3-5%

According to EC-Regulation 1907/2006 (REACH)

CLP CLASSIFICATION:	Flam. Liq. 2, STOT SE 3, Eye Irrit. 2 H225, H319, H336, EUH066
NOTE:	S
NAME:	PHENYL,BIS,2,4,6-TRIMETHYLBENZOYL,-PHOSPHINE,OXIDE
IDENTIFICATION NOS.:	CAS-no: 162881-26-7 EC-no: 423-340-5 REACH-no: 01-2119489401-38-0000 Index-no: 015-189-00-5
CONTENT:	1-3%
CLP CLASSIFICATION:	Skin Sens. 1, Aquatic Chronic 4 H317, H413
NAME:	2-benzyl-2-dimethylamino-4-morpholinobutyrophenone
IDENTIFICATION NOS.:	CAS-no: 119313-12-1 EC-no: 404-360-3 Index-no: 606-047-00-9
CONTENT:	<1%
CLP CLASSIFICATION:	Aquatic Chronic 1 H410

(*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.
S = Organic solvent

Other informations

ATEmix(inhale, vapour) > 20
ATEmix(oral) > 2000
Eye Cat. 2 Sum = $\sum(Ci/S(G)CLi) = 2,632 - 0$
Skin Cat. 2 Sum = $\sum(Ci/S(G)CLi) = 2,24 - 3,36$
N chronic (CAT 3) Sum = $\sum(Ci/M(chronic))^*25*0.1*10^{CATi} = 2,464 - 3,696$
N acute (CAT 1) Sum = $\sum(Ci/M(acute))^*25 = 0,01568 - 0,02352$

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

Inhalation

Get the injured person into fresh air. Make sure there is always someone with the injured person. Prevent shock by keeping the injured person warm and calm. If the person stops breathing, give mouth-to-mouth resuscitation. If unconscious, roll the injured person onto side with the top leg bent at both knee and hip. Call an ambulance.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes with water (20-30°C) for at least 15 minutes. Call a doctor.

Ingestion

In the case of ingestion, contact a doctor immediately and take this safety data sheet or the label from the material with you. If the person is conscious, give them water. DO NOT try to induce vomiting, unless this is recommended by a doctor. Hold head facing down so that no vomit runs back into the mouth and throat. Prevent shock by keeping the injured person warm and calm. Give mouth-to-mouth resuscitation if breathing stops. If unconscious, roll the injured person onto side with the top leg bent at both knee and hip. Call an ambulance.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can give chemical pneumonia if inhaled. The symptoms of chemical pneumonia can appear after several hours.

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc.

Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will

then be more prone to absorb dangerous substances, e.g. allergens.

Sensitivity effects: This product contains substances which can give an allergic reaction on contact with skin. The allergic reaction will typically set in 12-72 hours after exposure as the substance penetrates the skin and reacts with proteins in the outer skin. The body's immune system sees the chemically changed protein as a foreign body and will try to destroy it.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances. Avoid inhalation of vapours from waste material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of a leakage to the surroundings, contact the local environmental authorities. Consider putting up waste collecting trays/basins to prevent leakage to the surroundings.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

6.4. Reference to other sections

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Consider putting up waste collecting trays/basins to prevent leakage to the surroundings. See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original.

Please be aware that this is a chemical that forms peroxides. The content of peroxide must be controlled regularly after opening for example every 6th month.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

acetone propan-2-one propanone (EH40/2005)
Long-term exposure limit (8-hour TWA reference period): 500 ppm | 1210 mg/m³
Short-term exposure limit (15-minute reference period): 1500 ppm | 3620 mg/m³

styrene (EH40/2005)
Long-term exposure limit (8-hour TWA reference period): 100 ppm | 430 mg/m³
Short-term exposure limit (15-minute reference period): 250 ppm | 1080 mg/m³

DNEL / PNEC

DNEL (styrene): 406 mg/kg
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (styrene): 343 mg/kg
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - General population

DNEL (styrene): 2,1 mg/kg
Exposure: Oral
Duration of Exposure: Long term – Systemic effects - General population

DNEL (styrene): 85 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (styrene): 10,6 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - General population

DNEL (styrene): 289 mg/m³
Exposure: Inhalation
Duration of Exposure: Short term – Systemic effects - Workers

DNEL (styrene): 174,25 mg/m³
Exposure: Inhalation
Duration of Exposure: Short term – Systemic effects - General population

DNEL (styrene): 306 mg/m³
Exposure: Inhalation
Duration of Exposure: Short term – Local effects - Workers

DNEL (styrene): 182,75 mg/m³
Exposure: Inhalation
Duration of Exposure: Short term – Local effects - General population

DNEL (hexamethylene diacrylate hexane-1,6-diol diacrylate): 24,48 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers
DNEL (acetone propan-2-one propanone): 186 mg/kg
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (acetone propan-2-one propanone): 62 mg/kg
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - General population

DNEL (acetone propan-2-one propanone): 2420 mg/m³
Exposure: Inhalation
Duration of Exposure: Short term – Systemic effects - Workers

DNEL (acetone propan-2-one propanone): 1210 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (acetone propan-2-one propanone): 200 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - General population

DNEL (acetone propan-2-one propanone): 62 mg/kg
Exposure: Oral

According to EC-Regulation 1907/2006 (REACH)

Duration of Exposure: Long term – Systemic effects - General population
DNEL (PHENYL,BIS,2,4,6-TRIMETHYLBENZOYL,-PHOSPHINE,OXIDE): 7,8 mg/m³
Exposure: Inhalation
Duration of Exposure: Short term – Systemic effects - Workers

DNEL (PHENYL,BIS,2,4,6-TRIMETHYLBENZOYL,-PHOSPHINE,OXIDE): 7,8 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (PHENYL,BIS,2,4,6-TRIMETHYLBENZOYL,-PHOSPHINE,OXIDE): 3,3 mg/kg
Exposure: Dermal
Duration of Exposure: Short term – Systemic effects - Workers

DNEL (PHENYL,BIS,2,4,6-TRIMETHYLBENZOYL,-PHOSPHINE,OXIDE): 3,3 mg/kg
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - Workers

PNEC (styrene): 0,028 mg/L
Exposure: Freshwater

PNEC (styrene): 0,028 mg/L
Exposure: Marine water

PNEC (styrene): 0,614 mg/kg
Exposure: Freshwater sediment

PNEC (styrene): 0,0614 mg/kg
Exposure: Marine water sediment

PNEC (styrene): 0,2 mg/kg
Exposure: Soil

PNEC (hexamethylene diacrylate hexane-1,6-diol diacrylate): 0,0015 mg/L
Exposure: Freshwater

PNEC (hexamethylene diacrylate hexane-1,6-diol diacrylate): 0,00015 mg/L
Exposure: Marine water

PNEC (hexamethylene diacrylate hexane-1,6-diol diacrylate): 0,0137 mg/kg
Exposure: Soil

PNEC (acetone propan-2-one propanone): 21 mg/L
Exposure: Intermittent release

PNEC (acetone propan-2-one propanone): 30,4 mg/kg
Exposure: Freshwater sediment

PNEC (acetone propan-2-one propanone): 3,04 mg/kg
Exposure: Marine water sediment

PNEC (acetone propan-2-one propanone): 33,3 mg/kg
Exposure: Soil

PNEC (acetone propan-2-one propanone): 10,6 mg/kg
Exposure: Freshwater

PNEC (acetone propan-2-one propanone): 1,06 mg/kg
Exposure: Marine water

8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

General recommendations

Observe general occupational hygiene.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible collect spillage during work.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

Recommended: AX. Brown

Skin protection

Special work clothing should be used. When working with this product for a long period of time, use a protective suit.

Hand protection

Use protective gloves. The concrete work situation is not known. Contact the suppliers of the gloves for help on the glove type. Please note that elastic gloves stretch when used. The thickness of the gloves, and therefore their penetration time, will be reduced. Moreover, the temperature of the glove in use is about 35°C, while the standard test, EN 374-3, is done at 23°C. The penetration time is therefore reduced by a factor of 3.

Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm ³)
Pasta	Gray	Characteristic	-	-	1,36

Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-	56	180

Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
-15	-	465

Explosion limits (Vol %)	Oxidizing properties
2,5 - 14,3	-

Solubility

Solubility in water	n-octanol/water coefficient
Soluble	-

9.2. Other information

Solubility in fat	Additional information
-	N/A

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

No special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance	Species	Test	Route of exposure	Result
2-benzyl-2-dimethylamino-4-mo...	Rat	LD50		> 2000 mg/kg
2-benzyl-2-dimethylamino-4-mo...	Rat	LD50	Oral	> 5000 mg/kg
PHENYL,BIS,2,4,6-	Rat	LD50		> 2000 mg/kg
TRIMETHYLBENZ...	Rat	LD50	Oral	> 2000 mg/kg
PHENYL,BIS,2,4,6-	Rabbit	LD50		> 20 ml/kg
TRIMETHYLBENZ...	Rat	LD50		5500 mg/kg
acetone propan-2-one propan...	Rat	LD50	Oral	5800 mg/kg
acetone propan-2-one propan...	Rat	LC50	Inhalation	21,09 ppm/8H
acetone propan-2-one propan...	Rabbit	LD50		3650 mg/kg
acetone propan-2-one propan...	Rat	LD50	Oral	> 5000 mg/kg
hexamethylene diacrylate hex...	Rat	LD50		> 2000 mg/kg
hexamethylene diacrylate hex...	Rat	LD50	Intraperitoneal	898 mg/kg
styrene	Rat	LD50	Oral	5000 mg/kg
styrene	Rat	LC50	Inhalation	11,8 mg/L/4H
styrene				
styrene				

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction. Data on substance: hexamethylene diacrylate hexane-1,6-diol diacrylate

Organism: Guinea pig

Result: skin sensitizer

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

No data available.

STOT-repeated exposure

Causes damage to organs.

Aspiration hazard

May be fatal if swallowed and enters airways.

Long term effects

This product contains substances that can give chemical pneumonia if inhaled. The symptoms of chemical pneumonia can appear after several hours.

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system.

Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Sensitivity effects: This product contains substances which can give an allergic reaction on contact with skin. The allergic reaction will typically set in 12-72 hours after exposure as the substance penetrates the skin and reacts with proteins in the outer skin. The body's immune system sees the chemically changed protein as a foreign body and will try to destroy it.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Species	Test	Test duration	Result
2-benzyl-2-dimethylamino-4-mo...	Fish	LC50	96 h	0,46 mg/L
2-benzyl-2-dimethylamino-4-mo...	Daphnia	EC50	24 h	0,8 mg/L
2-benzyl-2-dimethylamino-4-mo...	Algae	EC50	72 h	2 mg/L
PHENYL,BIS,2,4,6-TRIMETHYLBENZ...	Daphnia	EC50	48 h	1,175 mg/L
PHENYL,BIS,2,4,6-TRIMETHYLBENZ...	Algae	EC50	72 h	0,260 mg/L
PHENYL,BIS,2,4,6-TRIMETHYLBENZ...	Fish	LC50	96 h	0,09 mg/L
PHENYL,BIS,2,4,6-TRIMETHYLBENZ...	Algae	EC50	120 H	14444 mg/L
acetone propan-2-one propan...	Crustacean	LC50	48 H	7550 mg/L
acetone propan-2-one propan...	Daphnia	EC50	48 h	13500 mg/L
acetone propan-2-one propan...	Daphnia	LC50	48 h	4700 µg/L
styrene	Fish	LC50	96 h	29000 µg/L
styrene				

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
acetone propan-2-one propan...	Yes	No data available	No data available

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BFC
acetone propan-2-one propan...	No	-0,24	No data available
styrene	No	2,95	No data available

12.4. Mobility in soil

acetone propan-2-one propan...: Log Koc= -0,111656, Calculated from LogPow (). styrene : Log Koc= 2,414505, Calculated from LogPow (Moderate mobility potential.).

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

This product contains ecotoxic substances which can have damaging effects on water-organisms. This product contains substances which can cause undesirable long-term effects in the water environment, due to its poor biodegradability.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

Waste

EWC code

-

Specific labelling

-

Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

SECTION 14: Transport information

This product is covered by the conventions on dangerous goods.

14.1 – 14.4

ADR/RID

14.1. UN number	1263
14.2. UN proper shipping name	PAINT
14.3. Transport hazard class(es)	3,2
14.4. Packing group	II
Notes	-
Tunnel restriction code	-

IMDG

According to EC-Regulation 1907/2006 (REACH)

UN-no.	1263
Proper Shipping Name	PAINT
Class	3,2
PG*	II
EmS	F-E, S-E
MP**	No
Hazardous constituent	-

▼ **IATA/ICAO**

UN-no.	
Proper Shipping Name	
Class	
PG*	

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC. Pregnant and nursing women must not be exposed to the effects of this product. The risk, and possible technical precautions or design of the workplace to avoid such risk, must therefore be evaluated.

Demands for specific education

-

Additional information

Sources

COUNCIL DIRECTIVE 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

IDirective 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

EC Regulation 1272/2008 (CLP).

EC regulation 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

According to EC-Regulation 1907/2006 (REACH)

H225 - Highly flammable liquid and vapour.
H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H372 - Causes damage to organs through prolonged or repeated exposure.
H410 - Very toxic to aquatic life with long lasting effects.
H412 - Harmful to aquatic life with long lasting effects.
H413 - May cause long lasting harmful effects to aquatic life.
EUH066 - Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

-

Other symbols mentioned in section 2

-

Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by

kbb

**Date of last essential change
(First cipher in SDS version)**

2016-01-28

**Date of last minor change
(Last cipher in SDS version)**

2016-01-28