

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

19010 - UV-A1 clear coat, aerosol

Product no.

19010

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

UV-A1 clear coat for autobody use

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

HBC System Smarttool Production ApS

Hobrovej 961-963

9530 Støvring

Denmark

tel:+45 70 22 70 70

Contact person

Vibeke Jørgensen

E-mail

info@hbc-system.com

SDS date

2016-05-27

SDS Version

3.0

1.4. Emergency telephone number

Use your national or local emergency number

See section 4 "First aid measures"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 1; H229

Aerosol 1; H222

Eye Irrit. 2; H319

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Pressurised container: May burst if heated. (H229)
 Extremely flammable aerosol. (H222)
 Causes serious eye irritation. (H319)

<p>General</p> <p>Prevention</p> <p>Safety statement(s)</p> <p>Response</p> <p>Storage</p> <p>Disposal</p>	<p>-</p> <p>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210). Do not spray on an open flame or other ignition source. (P211). Do not pierce or burn, even after use. (P251). Wear eye protection. (P280). If eye irritation persists: Get medical advice/attention. (P337+P313). Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412).</p> <p>-</p>
--	--

Identity of the substances primarily responsible for the major health hazards

-

2.3. Other hazards

This product contains an organic solvent. Repeated exposure to organic solvents can result in damage to the nervous system and inner organs, such as the liver and kidneys.

Additional labelling

Contains Hexane-1,6-diisocyanato-,homopolymer,2-hydroxyethyl,acrylate blocked. May produce an allergic reaction. Contains Ethyl phenyl(2,4,6-trimethylbenzoyl) phosphinate, Hexane-1,6-diisocyanato-,homopolymer,2-hydroxyethyl,acrylate blocked, hexamethylene diacrylate hexane-1,6-diol diacrylate, 2-Propenoic acid, reaction products with pentaerythritol, 1-acetyl-4-(3-dodecyl-2,5-dioxo-1-pyrrolidinyl)-2,2,6,6-tetramethylpiperidine. May produce an allergic reaction.

Additional warnings

-

VOC

VOC-MAX: 765 g/l, MAXIMUM VOC CONTENT (B/e): 840 g/l.

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

<p>NAME:</p> <p>IDENTIFICATION NOS.:</p> <p>CONTENT:</p> <p>CLP CLASSIFICATION:</p> <p>NOTE:</p>	<p>dimethyl ether</p> <p>CAS-no: 115-10-6 EC-no: 204-065-8 Index-no: 603-019-00-8</p> <p>80-95%</p> <p>Comp. Gas, Flam. Gas 1</p> <p>H220, H280</p> <p>S</p>
<p>NAME:</p> <p>IDENTIFICATION NOS.:</p> <p>CONTENT:</p> <p>CLP CLASSIFICATION:</p> <p>NOTE:</p>	<p>ethyl acetate</p> <p>CAS-no: 141-78-6 EC-no: 205-500-4 REACH-no: 01-2119475103-46 Index-no: 607-022-00-5</p> <p>5-10%</p> <p>Flam. Liq. 2, STOT SE 3, Eye Irrit. 2</p> <p>H225, H319, H336, EUH066</p> <p>S</p>
<p>NAME:</p> <p>IDENTIFICATION NOS.:</p> <p>CONTENT:</p> <p>CLP CLASSIFICATION:</p>	<p>(octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate</p> <p>CAS-no: 42594-17-2 EC-no: 255-901-3</p> <p>1-3%</p> <p>Skin Irrit. 2</p> <p>H315</p>
<p>NAME:</p> <p>IDENTIFICATION NOS.:</p> <p>CONTENT:</p> <p>CLP CLASSIFICATION:</p>	<p>2,4,6-trioxo-1,3,5-triazine-1,3,5,2H,4H,6H,-triyyl,tri-2,1-ethanediyl,triacrylate</p> <p>CAS-no: 40220-08-4 EC-no: 254-843-6</p> <p>1-3%</p> <p>Eye Dam. 1</p> <p>H318</p>
<p>NAME:</p> <p>IDENTIFICATION NOS.:</p> <p>CONTENT:</p> <p>CLP CLASSIFICATION:</p>	<p>Hexane-1,6-diisocyanato-,homopolymer,2-hydroxyethyl,acrylate blocked</p> <p>CAS-no: 264888-31-5</p> <p><1%</p> <p>Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1</p> <p>H315, H317, H319, H334</p>

According to EC-Regulation 1907/2006 (REACH)

NAME:	Ethyl phenyl(2,4,6-trimethylbenzoyl) phosphinate
IDENTIFICATION NOS.:	CAS-no: 84434-11-7 EC-no: 282-810-6
CONTENT:	<1%
CLP CLASSIFICATION:	Skin Sens. 1, Aquatic Chronic 2 H317, H411
NAME:	hexamethylene diacrylate hexane-1,6-diol diacrylate
IDENTIFICATION NOS.:	CAS-no: 13048-33-4 EC-no: 235-921-9 REACH-no: 01-2119484737-22 Index-no: 607-109-00-8
CONTENT:	<1%
CLP CLASSIFICATION:	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3 H315, H317, H319, H412
NAME:	2-Propenoic acid, reaction products with pentaerythritol
IDENTIFICATION NOS.:	CAS-no: 1245638-61-2 REACH-no: 01-2119490003-49
CONTENT:	<1%
CLP CLASSIFICATION:	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 2 H302, H315, H317, H318, H411
NAME:	1-acetyl-4-(3-dodecyl-2,5-dioxo-1-pyrrolidinyl)-2,2,6,6-tetramethylpiperidine
IDENTIFICATION NOS.:	CAS-no: 106917-31-1 EC-no: 411-930-5 REACH-no: 01-0000015927-59 Index-no: 613-229-00-1
CONTENT:	<1%
CLP CLASSIFICATION:	Skin Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1 H315, H317, H400, H410

(*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.

S = Organic solvent

Other informations

ATEmix(inhale, vapour) > 20
 ATEmix(dermal) > 2000
 ATEmix(oral) > 2000
 Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 1,7736 - 0,5304
 Skin Cat. 2 Sum = Sum(Ci/S(G)CLi) = 0,1176 - 0,1764
 N chronic (CAT 4) Sum = Sum(Ci/M(chronic)ⁱ*25*0,1*10[^]CAT4) = 0,003764192 - 0,005646288
 N acute (CAT 1) Sum = Sum(Ci/M(acute)ⁱ*25) = 0,003764192 - 0,005646288

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.
 Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

Inhalation

Get the person into fresh air and stay with them.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes with water (20-30°C) for at least 15 minutes. Call a doctor.

Ingestion

Give the person plenty to drink and stay with the person. If the person feels unwell, contact a doctor immediately and take this safety data sheet or the label from the product with you. Do not induce vomiting unless recommended by the doctor. Hold head facing down so that no vomit runs back into the mouth and throat.

Burns

Rinse with water until the pain stops and continue for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

This product contains substances that may cause an allergic reaction in people who are already so disposed.

Sensitivity effects: This product contains substances which can give an allergic reaction when inhaled. The allergic reaction allergy will typically set in an hour after exposure and give an inflammatory reaction in the lungs.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Nitrogen oxides. Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stores that have not ignited must be cooled by water mist. Where possible, remove flammable materials. Make sure there is sufficient ventilation.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

6.4. Reference to other sections

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original. Must be stored in a cool and ventilated area, away from possible sources of combustion.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

ethyl acetate (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 200 ppm | - mg/m³

Short-term exposure limit (15-minute reference period): 400 ppm | - mg/m³

dimethyl ether (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 400 ppm | 766 mg/m³

Short-term exposure limit (15-minute reference period): 500 ppm | 958 mg/m³

DNEL / PNEC

DNEL (ethyl acetate): 734 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - General population

DNEL (ethyl acetate): 1468 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (ethyl acetate): 4,5 mg/kg

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (ethyl acetate): 734 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (ethyl acetate): 367 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - General population

DNEL (ethyl acetate): 1468 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

DNEL (ethyl acetate): 734 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - General population

DNEL (ethyl acetate): 63 mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (ethyl acetate): 37 mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (ethyl acetate): 734 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (ethyl acetate): 367 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (hexamethylene diacrylate hexane-1,6-diol diacrylate): 24,48 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-Propenoic acid, reaction products with pentaerythritol): 1,04 mg/kg

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-Propenoic acid, reaction products with pentaerythritol): 7,35 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

PNEC (ethyl acetate): 0,26 mg/L

Exposure: Freshwater

PNEC (ethyl acetate): 0,026 mg/L

Exposure: Marine water

PNEC (ethyl acetate): 1,65 mg/L

Exposure: Intermittent release

PNEC (ethyl acetate): 1,25 mg/kg

Exposure: Freshwater sediment

PNEC (ethyl acetate): 0,125 mg/kg

Exposure: Marine water sediment

PNEC (ethyl acetate): 0,24 mg/kg

According to EC-Regulation 1907/2006 (REACH)

Exposure: Soil

PNEC (hexamethylene diacrylate hexane-1,6-diol diacrylate): 0,0015 mg/L
Exposure: Freshwater

PNEC (hexamethylene diacrylate hexane-1,6-diol diacrylate): 0,00015 mg/L
Exposure: Marine water

PNEC (hexamethylene diacrylate hexane-1,6-diol diacrylate): 0,0137 mg/kg
Exposure: Soil

PNEC (2-Propenoic acid, reaction products with pentaerythritol): 0,0032 mg/L
Exposure: Freshwater

8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

General recommendations

Observe general occupational hygiene.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

If the ventilation at the work place is not sufficient, use a half or whole mask with an appropriate filter or an air-supplied respiratory protector. The choice depends on the concrete work situation and how long you will be using the product.

Skin protection

Special work clothing should be used.

Hand protection

Use protective gloves. The concrete work situation is not known. Contact the suppliers of the gloves for help on the glove type. Please note that elastic gloves stretch when used. The thickness of the gloves, and therefore their penetration time, will be reduced. Moreover, the temperature of the glove in use is about 35°C, while the standard test, EN 374-3, is done at 23°C. The penetration time is therefore reduced by a factor of 3.

Eye protection

Use safety glasses with a side shield.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm ³)
Aerosol	-	-	-	-	0,8

Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-	-	-

Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
-	-	-
Explosion limits (Vol %)	Oxidizing properties	
-	-	

Solubility

Solubility in water	n-octanol/water coefficient
Soluble	-

9.2. Other information

Solubility in fat	Additional information
-	N/A

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance	Species	Test	Route of exposure	Result
1-acetyl-4-(3-dodecyl-2,5-diox...	Rat	LD50	Oral	> 3000 mg/kg
1-acetyl-4-(3-dodecyl-2,5-diox...	Rat	LC50	Inhalation	2,61 mg/L/4h
2-Propenoic acid, reaction pro...	Rabbit	LD50		> 2000 mg/kg
2-Propenoic acid, reaction pro...	Rat	LD50	Oral	540-1350 mg/kg
hexamethylene diacrylate hex...	Rabbit	LD50		3650 mg/kg
hexamethylene diacrylate hex...	Rat	LD50	Oral	> 5000 mg/kg
ethyl acetate	Rabbit	LD50	Oral	4935 mg/kg
ethyl acetate	Rat	LD50	Oral	11,3 g/kg
ethyl acetate	Guinea pig	LD50	Intraperitoneal	709 mg/kg
ethyl acetate	Rat	LC50	Inhalation	1600 mg/L
dimethyl ether	Rabbit	LC50	Inhalation	308 g/m ³

Skin corrosion/irritation

Data on substance: 1-acetyl-4-(3-dodecyl-2,5-dioxo-1-pyrrolidinyl)-2,2,6,6-tetramethylpiperidine

Result: Skin irritant

Serious eye damage/irritation

Causes serious eye irritation.

Data on substance: 2,4,6-trioxo-1,3,5-triazine-1,3,5,2H,4H,6H,-triyli,tri-2,1-ethanediyl,triacrylate

Organism: Rabbit

Result: Eye irritant

Respiratory or skin sensitisation

Data on substance: 1-acetyl-4-(3-dodecyl-2,5-dioxo-1-pyrrolidinyl)-2,2,6,6-tetramethylpiperidine

Data on substance: 1-acetyl-4-(3-dodecyl-2,5-dioxo-1-pyrrolidinyl)-2,2,6,6-tetramethylpiperidine

Data on substance: 2-Propenoic acid, reaction products with pentaerythritol
Result: skin sensitizer

Data on substance: hexamethylene diacrylate hexane-1,6-diol diacrylate
Organism: Guinea pig
Result: skin sensitizer

Data on substance: (octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate
Result: Skin Irritant

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

This product contains substances that may cause an allergic reaction in people who are already so disposed. Sensitivity effects: This product contains substances which can give an allergic reaction when inhaled. The allergic reaction allergy will typically set in an hour after exposure and give an inflammatory reaction in the lungs.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Species	Test	Test duration	Result
1-acetyl-4-(3-dodecyl-2,5-diox...	Fish	LC50	96 h	> 0,5 mg/L
1-acetyl-4-(3-dodecyl-2,5-diox...	Daphnia	EC50	48h	0,27 mg/L
Ethyl phenyl(2,4,6-trimethylbe...	Daphnia	EC50	48 h	10 mg/L
ethyl acetate	Algae	EC50	48 H	330000 ug/L
ethyl acetate	Daphnia	LC50	48 H	560000 ug/L
ethyl acetate	Fish	LC50	96 H	425300 ug/L

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
No data available.			

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BFC
dimethyl ether	No	0,1	No data available

12.4. Mobility in soil

dimethyl ether : Log Koc= 0,15759, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

According to EC-Regulation 1907/2006 (REACH)

This product contains ecotoxic substances which can have damaging effects on water-organisms. This product contains substances which can cause undesirable long-term effects in the water environment, due to its poor biodegradability.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

Waste

EWC code

-

Specific labelling

-

Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

SECTION 14: Transport information

This product is covered by the conventions on dangerous goods.

14.1 – 14.4

ADR/RID

14.1. UN number	1950
14.2. UN proper shipping name	AEROSOLS, Flammable
14.3. Transport hazard class(es)	2,1
14.4. Packing group	-
Notes	-
Tunnel restriction code	-

IMDG

UN-no.	1950
Proper Shipping Name	AEROSOLS, Flammable
Class	2,1
PG*	-
EmS	F-D, S-U
MP**	No
Hazardous constituent	-

IATA/ICAO

UN-no.	
Proper Shipping Name	
Class	
PG*	

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC.

Demands for specific education

-

Additional information

Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.
Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers.
Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.
EC Regulation 1272/2008 (CLP).
EC regulation 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H220 - Extremely flammable gas.
H225 - Highly flammable liquid and vapour.
H280 - Contains gas under pressure; may explode if heated.
H302 - Harmful if swallowed.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H319 - Causes serious eye irritation.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336 - May cause drowsiness or dizziness.
H400 - Very toxic to aquatic life.
H410 - Very toxic to aquatic life with long lasting effects.
H411 - Toxic to aquatic life with long lasting effects.
H412 - Harmful to aquatic life with long lasting effects.
EUH066 - Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

-

Other symbols mentioned in section 2



Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by

kbb

Date of last essential change (First cipher in SDS version)

2016-03-01

Date of last minor change (Last cipher in SDS version)

2016-03-01