

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

301 - PVC sanding

**Product no.**

00.301

**REACH registration number**

Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Plast primer and sanding agent

**Uses advised against**

-

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

**Company and address**

HBC System Smarttool Production ApS

Hobrovej 961-963

9530 Støvring

Denmark

tel:+45 70 22 70 70

**Contact person**

Vibeke Jørgensen

**E-mail**

info@hbc-system.com

**SDS date**

2016-01-13

**SDS Version**

3.0

### 1.4. Emergency telephone number

Use your national or local emergency number

See section 4 "First aid measures"

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Aerosol 1; H229

Aerosol 1; H222

See full text of H-phrases in section 2.2.

### 2.2. Label elements

**Hazard pictogram(s)**



**Signal word**

Danger

**Hazard statement(s)**

Pressurised container: May burst if heated. (H229)  
Extremely flammable aerosol. (H222)

<b>Safety statement(s)</b>	<b>General</b>	If medical advice is needed, have product container or label at hand. (P101). Keep out of reach of children. (P102).
	<b>Prevention</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210). Do not spray on an open flame or other ignition source. (P211). Do not pierce or burn, even after use. (P251).
	<b>Response</b>	-
	<b>Storage</b>	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412).
	<b>Disposal</b>	-

**Identity of the substances primarily responsible for the major health hazards**

-

**2.3. Other hazards**

This product contains teratogenic substances, which can cause long-term damage to the human embryo.  
The product contains substances that can damage the reproductive system.

This product contains an organic solvent. Repeated exposure to organic solvents can result in damage to the nervous system and inner organs, such as the liver and kidneys.

**Additional labelling**

-

**Additional warnings**

Tactile warning.

**VOC**

-

**SECTION 3: Composition/information on ingredients**

**▼ 3.1/3.2. Substances/Mixtures**

NAME:	dimethyl ether
IDENTIFICATION NOS.:	CAS-no: 115-10-6 EC-no: 204-065-8 Index-no: 603-019-00-8
CONTENT:	40-60%
CLP CLASSIFICATION:	Comp. Gas, Flam. Gas 1 H220, H280
NOTE:	S
NAME:	n-butyl acetate
IDENTIFICATION NOS.:	CAS-no: 123-86-4 EC-no: 204-658-1 REACH-no: 01-2119485493-29 Index-no: 607-025-00-1
CONTENT:	10-15%
CLP CLASSIFICATION:	Flam. Liq. 3, STOT SE 3 H226, H336, EUH066
NOTE:	S
NAME:	Xylene, mixture of isomers
IDENTIFICATION NOS.:	CAS-no: 1330-20-7 EC-no: 215-535-7 REACH-no: 01-2119488216-32 Index-no: 601-022-00-9
CONTENT:	5-10%
CLP CLASSIFICATION:	Flam. Liq. 3, Acute Tox. 4, STOT RE 2, STOT SE 3, Skin Irrit. 2, Eye Irrit. 2 H226, H312, H315, H319, H332, H335, H373
NOTE:	S
NAME:	2-methoxy-1-methylethyl acetate
IDENTIFICATION NOS.:	CAS-no: 108-65-6 EC-no: 203-603-9 REACH-no: 01-2119475791-29-xxxx Index-no: 607-195-00-7
CONTENT:	1-3%
CLP CLASSIFICATION:	Flam. Liq. 3 H226
NOTE:	S
NAME:	4-methylpentan-2-one isobutyl methyl ketone
IDENTIFICATION NOS.:	CAS-no: 108-10-1 EC-no: 203-550-1 Index-no: 606-004-00-4
CONTENT:	1-3%
CLP CLASSIFICATION:	Flam. Liq. 2, Acute Tox. 4, STOT SE 3, Eye Irrit. 2 H225, H302, H319, H332, H335, EUH066
NOTE:	S

According to EC-Regulation 1907/2006 (REACH)

NAME:	toluene
IDENTIFICATION NOS.:	CAS-no: 108-88-3 EC-no: 203-625-9 Index-no: 601-021-00-3
CONTENT:	<1%
CLP CLASSIFICATION:	Flam. Liq. 2, STOT RE 2, STOT SE 3, Skin Irrit. 2, Asp. Tox. 1, Repr. 2 H225, H304, H315, H336, H361, H373
NOTE:	S

(\*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.

S = Organic solvent

### Other informations

ATEmix(inhale, vapour) > 20  
ATEmix(inhale, dust/mist) > 20000  
ATEmix(dermal) > 2000  
ATEmix(oral) > 2000  
Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 0,564 - 0,846  
Skin Cat. 2 Sum = Sum(Ci/S(G)CLi) = 0,4664 - 0,6996

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

#### Inhalation

Get the person into fresh air and stay with them.

#### Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

#### Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. If irritation continues, contact a doctor.

#### Ingestion

Give the person plenty to drink and stay with the person. If the person feels unwell, contact a doctor immediately and take this safety data sheet or the label from the product with you. Do not induce vomiting unless recommended by the doctor. Hold head facing down so that no vomit runs back into the mouth and throat.

#### Burns

Rinse with water until the pain stops and continue for 30 minutes.

### 4.2. Most important symptoms and effects, both acute and delayed

Reproductive toxicity: This product contains teratogenic substances which can do long-term damage to human offspring. The effects on the child can be: death, deformity, delayed development, and functional disorders.

Reproductive toxicity: This product contains substances which can do damage to reproductive capacity, e.g. damage to germ cells or hormonal regulation. The effects can be: sterility, reduced fertility, menstruation disorders, etc.

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc.

Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

### 4.3. Indication of any immediate medical attention and special treatment needed

No special

#### Information to medics

Bring this safety data sheet.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used,

since they can spread the fire.

### 5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stores that have not ignited must be cooled by water mist. Where possible, remove flammable materials. Make sure there is sufficient ventilation.

### 6.2. Environmental precautions

No specific requirements.

### 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

### 6.4. Reference to other sections

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

See section on 'Exposure controls/personal protection' for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original. Must be stored in a cool and ventilated area, away from possible sources of combustion.

Please be aware that this is a chemical that forms peroxides. The content of peroxide must be controlled regularly after opening for example every 6th month.

#### Storage temperature

No data available.

### 7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### OEL

toluene (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 191 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 100 ppm | 384 mg/m<sup>3</sup>

Comments: Sk (Sk = Can be absorbed through skin. )

ethylbenzene (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 100 ppm | 441 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 125 ppm | 552 mg/m<sup>3</sup>

Comments: Sk (Sk = Can be absorbed through skin. )

4-methylpentan-2-one isobutyl methyl ketone (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 208 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 100 ppm | 416 mg/m<sup>3</sup>

Comments: sk bmgv (Bmgv = Biological Monitoring Guidance Value. Sk = Can be absorbed through skin. )

2-methoxy-1-methylethyl acetate (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 274 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 100 ppm | 548 mg/m<sup>3</sup>

Comments: Sk (Sk = Can be absorbed through skin. )

Xylene, mixture of isomeres (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 220 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 100 ppm | 441 mg/m<sup>3</sup>

Comments: Sk BMGV (Bmgv = Biological Monitoring Guidance Value. Sk = Can be absorbed through skin. )

n-butyl acetate (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 150 ppm | 724 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 200 ppm | 966 mg/m<sup>3</sup>

dimethyl ether (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 400 ppm | 766 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 500 ppm | 958 mg/m<sup>3</sup>

## DNEL / PNEC

DNEL (Xylene, mixture of isomeres): 77 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

Remarks: workers

DNEL (Xylene, mixture of isomeres): 289 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

Remarks: workers - irritation (respiratory tract) - data from the registration

DNEL (Xylene, mixture of isomeres): 180 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

Remarks: workers - data from the registration

DNEL (Xylene, mixture of isomeres): 1,6 mg/kg bw/day

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Xylene, mixture of isomeres): 108 mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Xylene, mixture of isomeres): 14,8 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Xylene, mixture of isomeres): 289 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (Xylene, mixture of isomeres): 174 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - General population

DNEL (Xylene, mixture of isomeres): 174 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - General population

DNEL (n-butyl acetate): 102,34 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (n-butyl acetate): 960 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

DNEL (n-butyl acetate): 960 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (n-butyl acetate): 480 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (n-butyl acetate): 480 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (n-butyl acetate): 859,7 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - General population

DNEL (n-butyl acetate): 102,34 mg/m<sup>3</sup>  
Exposure: Inhalation  
Duration of Exposure: Long term – Local effects - General population

DNEL (n-butyl acetate): 859,7 mg/m<sup>3</sup>  
Exposure: Inhalation  
Duration of Exposure: Short term – Local effects - General population  
DNEL ( toluene ): 384 mg/m<sup>3</sup>  
Exposure: Inhalation  
Duration of Exposure: Short term – Local effects - Workers

DNEL ( toluene ): 384 mg/m<sup>3</sup>  
Exposure: Inhalation  
Duration of Exposure: Short term – Systemic effects - Workers

DNEL ( toluene ): 192 mg/m<sup>3</sup>  
Exposure: Inhalation  
Duration of Exposure: Long term – Local effects - Workers

DNEL ( toluene ): 384 mg/kg bw/day  
Exposure: Dermal  
Duration of Exposure: Long term – Systemic effects - Workers

DNEL ( toluene ): 226 mg/m<sup>3</sup>  
Exposure: Inhalation  
Duration of Exposure: Short term – Local effects - Workers

DNEL ( toluene ): 226 mg/m<sup>3</sup>  
Exposure: Inhalation  
Duration of Exposure: Short term – Systemic effects - Workers

DNEL ( toluene ): 56,5 mg/m<sup>3</sup>  
Exposure: Inhalation  
Duration of Exposure: Long term – Systemic effects - General population

DNEL ( toluene ): 226 mg/kg bw/day  
Exposure: Dermal  
Duration of Exposure: Long term – Systemic effects - General population

DNEL ( toluene ): 8,13 mg/kg bw/day  
Exposure: Oral  
Duration of Exposure: Long term – Systemic effects - General population

PNEC (Xylene, mixture of isomeres): 0.327 mg/l  
Exposure: Freshwater

PNEC (Xylene, mixture of isomeres): 6,58 mg/L  
Exposure: Sewage Treatment Plant

PNEC (Xylene, mixture of isomeres): 0,327 mg/L  
Exposure: Marine water

PNEC (Xylene, mixture of isomeres): 0,327 mg/L  
Exposure: Intermittent release

PNEC (Xylene, mixture of isomeres): 12,46 mg/kg  
Exposure: Freshwater sediment

PNEC (Xylene, mixture of isomeres): 12,46 mg/kg  
Exposure: Marine water sediment

PNEC (Xylene, mixture of isomeres): 2,31 mg/kg  
Exposure: Soil

PNEC (n-butyl acetate): 35,6 mg/L  
Exposure: Sewage Treatment Plant

PNEC (n-butyl acetate): 0,18 mg/L  
Exposure: Freshwater

PNEC (n-butyl acetate): 0,018 mg/L  
Exposure: Marine water

According to EC-Regulation 1907/2006 (REACH)

PNEC (n-butyl acetate): 0,36 mg/L  
Exposure: Intermittent release

PNEC (n-butyl acetate): 0,981 mg/kg  
Exposure: Freshwater sediment

PNEC (n-butyl acetate): 0,0981 mg/kg  
Exposure: Marine water sediment

PNEC (n-butyl acetate): 0,09903 mg/kg  
Exposure: Soil

PNEC ( toluene ): 0,68 mg/L  
Exposure: Freshwater

PNEC ( toluene ): 0,68 mg/L  
Exposure: Marine water

PNEC ( toluene ): 16,39 mg/L  
Exposure: Freshwater sediment

PNEC ( toluene ): 2,89 mg/kg  
Exposure: Soil

PNEC ( toluene ): 13,61 mg/L  
Exposure: Sewage Treatment Plant

## 8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

### General recommendations

Observe general occupational hygiene.

### Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

### Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

### Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

### Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

### Measures to avoid environmental exposure

No specific requirements.

### Individual protection measures, such as personal protective equipment



### Generally

Use only CE marked protective equipment.

### Respiratory Equipment

If the ventilation at the work place is not sufficient, use a half or whole mask with an appropriate filter or an air-supplied respiratory protector. The choice depends on the concrete work situation and how long you will be using the product.

### Skin protection

No specific requirements.

### Hand protection

Use protective gloves. The concrete work situation is not known. Contact the suppliers of the gloves for

According to EC-Regulation 1907/2006 (REACH)

help on the glove type. Please note that elastic gloves stretch when used. The thickness of the gloves, and therefore their penetration time, will be reduced. Moreover, the temperature of the glove in use is about 35°C, while the standard test, EN 374-3, is done at 23°C. The penetration time is therefore reduced by a factor of 3.

#### Eye protection

Use safety glasses with a side shield.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm <sup>3</sup> )
Aerosol	-	-	-	-	-

#### Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-	-	-

#### Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
-	-	-

Explosion limits (Vol %)	Oxidizing properties
-	-

#### Solubility

Solubility in water	n-octanol/water coefficient
Soluble	-

#### 9.2. Other information

Solubility in fat	Additional information
-	N/A

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No data available

#### 10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

#### 10.3. Possibility of hazardous reactions

No special

#### 10.4. Conditions to avoid

Avoid static electricity.

#### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

#### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

Substance	Species	Test	Route of exposure	Result
toluene	Rat	LD50	Oral	636 mg/kg
toluene	Rabbit	LD50	Dermal	> 5000 mg/kg
toluene	Rat	LC50	Inhalation	28,1 mg/L/4H
4-methylpentan-2-one isobuty...	Guinea pig	LD50	Oral	1900 mg/kg
4-methylpentan-2-one isobuty...	Guinea pig	LD50	Intraperitoneal	268 mg/kg
4-methylpentan-2-one isobuty...	Guinea pig	LC50	Inhalation	23300 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetat...	Rat	LD50	Oral	8532 mg/kg
2-methoxy-1-methylethyl acetat...	Rabbit	LD50		> 5000 mg/kg
2-methoxy-1-methylethyl acetat...	Guinea pig	LD50	Intraperitoneal	750 mg/kg
Xylene, mixture of isomeres	Rabbit	LD50		4350 mg/kg
Xylene, mixture of isomeres	Guinea pig	LD50	Oral	5251 mg/kg bw
Xylene, mixture of isomeres	Rabbit	LD50	Dermal	(female)
Xylene, mixture of isomeres	Rat	LD50	Inhalation	> 1,7 g/kg
Xylene, mixture of isomeres	Rat	LD50	Oral	5000 ppm
Xylene, mixture of isomeres	Guinea pig	LD50	Intraperitoneal	3523 mg/kg
n-butyl acetate	Rat	LD50	Oral	1548 mg/kg

According to EC-Regulation 1907/2006 (REACH)

n-butyl acetate	Rabbit	LD50		10768 g/kg
n-butyl acetate	Rat	LD50	Oral	> 5000 mg/kg
n-butyl acetate	Rat	LC50	Inhalation	> 6400 mg/kg
n-butyl acetate	Rat	LC50	Inhalation	2000 ppm
dimethyl ether	Rabbit	LC50	Inhalation	21.1 mg/l/4h
				308 g/m <sup>3</sup>

**Skin corrosion/irritation**

No data available.

**Serious eye damage/irritation**

No data available.

**Respiratory or skin sensitisation**

No data available.

**Germ cell mutagenicity**

No data available.

**Carcinogenicity**

No data available.

**Reproductive toxicity**

No data available.

**STOT-single exposure**

No data available.

**STOT-repeated exposure**

No data available.

**Aspiration hazard**

No data available.

**Long term effects**

Reproductive toxicity: This product contains teratogenic substances which can do long-term damage to human offspring. The effects on the child can be: death, deformity, delayed development, and functional disorders.

Reproductive toxicity: This product contains substances which can do damage to reproductive capacity, e.g. damage to germ cells or hormonal regulation. The effects can be: sterility, reduced fertility, menstruation disorders, etc.

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Substance	Species	Test	Test duration	Result
toluene	Daphnia	LC50	48h	3,8 mg/L
toluene	Fish	LC50	96h	5,5 mg/L
toluene	Algae	EC50	72 h	12,5 mg/L
4-methylpentan-2-one isobuty...	Daphnia	EC50	24 H	1550 mg/L
4-methylpentan-2-one isobuty...	Fish	LC50	96 H	540 mg/L
2-methoxy-1-methylethyl acetat...	Fish	LC50	96 h	120 ug/L
Xylene, mixture of isomeres	Crustacean	EC50	48 H	90000 µg/L
Xylene, mixture of isomeres	Daphnia	LC50	24 H	150 mg/L
Xylene, mixture of isomeres	Fish	LC50	96 H	13500 µg/L
n-butyl acetate	Daphnia	EC50	24 H	205 mg/L
n-butyl acetate	Fish	LC50	96 H	100 mg/L
n-butyl acetate	Crustacean	LC50	48 h	32000 ug/L

**12.2. Persistence and degradability**

Substance	Biodegradability	Test	Result
n-butyl acetate	Yes	No data available	No data available

**12.3. Bioaccumulative potential**

Substance	Potential bioaccumulation	LogPow	BFC
-----------	---------------------------	--------	-----

According to EC-Regulation 1907/2006 (REACH)

toluene	Yes	2,73	No data available
4-methylpentan-2-one isobuty...	No	1,31	No data available
2-methoxy-1-methylethyl acetat...	No	0,56	No data available
Xylene, mixture of isomers	Yes	3,16	No data available
n-butyl acetate	No	1,78	No data available
dimethyl ether	No	0,1	No data available

#### 12.4. Mobility in soil

toluene : Log Koc= 2,240287, Calculated from LogPow (Moderate mobility potential.). 4-methylpentan-2-one isobuty...: Log Koc= 1,115789, Calculated from LogPow (High mobility potential.). 2-methoxy-1-methylethyl acetat...: Log Koc= 0,521864, Calculated from LogPow (High mobility potential.). Xylene, mixture of isomers: Log Koc= 2,580804, Calculated from LogPow (Moderate mobility potential.). n-butyl acetate: Log Koc= 1,487982, Calculated from LogPow (High mobility potential.). dimethyl ether : Log Koc= 0,15759, Calculated from LogPow (High mobility potential.).

#### 12.5. Results of PBT and vPvB assessment

No data available

#### 12.6. Other adverse effects

This product contains substances which can accumulate in the food chain because they are bioaccumulative substances. Bioaccumulative substances can accumulate in fat tissue and are not easily secreted.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

##### Waste

EWC code

08 01 11

##### Specific labelling

-

##### Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

### SECTION 14: Transport information

This product is covered by the conventions on dangerous goods.

#### 14.1 – 14.4

##### ADR/RID

14.1. UN number	1263
14.2. UN proper shipping name	PAINT RELATED MATERIAL
14.3. Transport hazard class(es)	3
14.4. Packing group	III
Notes	-
Tunnel restriction code	-

##### IMDG

UN-no.	1263
Proper Shipping Name	PAINT RELATED MATERIAL
Class	3
PG*	III
EmS	F-E, S-E
MP**	-
Hazardous constituent	-

##### IATA/ICAO

UN-no.	
Proper Shipping Name	
Class	
PG*	

#### 14.5. Environmental hazards

-

#### 14.6. Special precautions for user

-  
**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

No data available

(\*) Packing group

(\*\*) Marine pollutant

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Restrictions for application**

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC.

**Demands for specific education**

-  
**Additional information**

**Sources**

COUNCIL DIRECTIVE 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers.

EC Regulation 1272/2008 (CLP).

EC regulation 1907/2006 (REACH).

**15.2. Chemical safety assessment**

No

**SECTION 16: Other information**

**Full text of H-phrases as mentioned in section 3**

H220 - Extremely flammable gas.

H225 - Highly flammable liquid and vapour.

H226 - Flammable liquid and vapour.

H280 - Contains gas under pressure; may explode if heated.

H302 - Harmful if swallowed.

H304 - May be fatal if swallowed and enters airways.

H312 - Harmful in contact with skin.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

H335 - May cause respiratory irritation.

H336 - May cause drowsiness or dizziness.

H361 - Suspected of damaging fertility or the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure.

EUH066 - Repeated exposure may cause skin dryness or cracking.

**The full text of identified uses as mentioned in section 1**

-  
**Other symbols mentioned in section 2**



**Other**

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

According to EC-Regulation 1907/2006 (REACH)



A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

**The safety data sheet is validated by**

kbb

**Date of last essential change**

**(First cipher in SDS version)**

2015-11-24

**Date of last minor change**

**(Last cipher in SDS version)**

2015-11-24

---

ALPHAOMEGA. Licens nr.:3003391770, HBC SYSTEM Danmark  
[www.chymeia.com](http://www.chymeia.com)