

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

B3 Solvent Colour Coat

Product no.

26-34, 148-149

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Industrial use

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

HBC System Smarttool Production ApS

Hobrovej 961-963

9530 Støvring

Denmark

tel:+45 70 22 70 70

Contact person

Vibeke Jørgensen

E-mail

info@hbc-system.com

SDS date

2016-06-30

SDS Version

1.0

1.4. Emergency telephone number

Use your national or local emergency number

See section 4 "First aid measures"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225

Repr. 2; H361

STOT RE 2; H373

Asp. Tox. 1; H304

Skin Irrit. 2; H315

STOT SE 3; H336

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

- Highly flammable liquid and vapour. (H225)
- Suspected of damaging fertility or the unborn child. (H361)
- May cause damage to organs through prolonged or repeated exposure. (H373)
- May be fatal if swallowed and enters airways. (H304)
- Causes skin irritation. (H315)
- May cause drowsiness or dizziness. (H336)

Safety statement(s)	General	-
	Prevention	Obtain special instructions before use. (P201). Use personal protective equipment as required. (P281).
	Response	Do NOT induce vomiting. (P331). IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310).
	Storage	Store in a well-ventilated place. Keep cool. (P403+P235).
	Disposal	Dispose of contents/container to an approved waste disposal plant. (P501).

Identity of the substances primarily responsible for the major health hazards

toluene

2.3. Other hazards

This product contains teratogenic substances, which can cause long-term damage to the human embryo.
 This product contains substances that can give chemical pneumonia if inhaled. The symptoms of chemical pneumonia can appear after several hours.
 The product contains substances that can damage the reproductive system.
 This product contains an organic solvent. Repeated exposure to organic solvents can result in damage to the nervous system and inner organs, such as the liver and kidneys.

Additional labelling

-

Additional warnings

-

VOC

VOC-MAX: 750 g/l, MAXIMUM VOC CONTENT (B/e): 840 g/l.

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME:	toluene
IDENTIFICATION NOS.:	CAS-no: 108-88-3 EC-no: 203-625-9 Index-no: 601-021-00-3
CONTENT:	60-80%
CLP CLASSIFICATION:	Flam. Liq. 2, STOT RE 2, STOT SE 3, Skin Irrit. 2, Asp. Tox. 1, Repr. 2 H225, H304, H315, H336, H361, H373
NOTE:	S

(*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.
 S = Organic solvent

Other informations

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

Inhalation

Get the person into fresh air and stay with them.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. If irritation continues, contact a doctor.

Ingestion

In the case of ingestion, contact a doctor immediately and take this safety data sheet or the label from the material with you. If the person is conscious, give them water. DO NOT try to induce vomiting, unless this is recommended by a doctor. Hold head facing down so that no vomit runs back into the mouth and throat. Prevent shock by keeping the injured person warm and calm. Give mouth-to-mouth resuscitation if breathing stops. If unconscious, roll the injured person onto side with the top leg bent at both knee and hip. Call an ambulance.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Rinse with water until the pain stops and continue for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Reproductive toxicity: This product contains teratogenic substances which can do long-term damage to human offspring. The effects on the child can be: death, deformity, delayed development, and functional disorders.

This product contains substances that can give chemical pneumonia if inhaled. The symptoms of chemical pneumonia can appear after several hours.

Reproductive toxicity: This product contains substances which can do damage to reproductive capacity, e.g. damage to germ cells or hormonal regulation. The effects can be: sterility, reduced fertility, menstruation disorders, etc.

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc.

Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours from waste material. Avoid direct contact with spilled substances. Stores that have not ignited must be cooled by water mist. Where possible, remove flammable materials. Make sure there is sufficient ventilation.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

6.4. Reference to other sections

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original. Must be stored in a cool and ventilated area, away from possible sources of combustion.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

toluene (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 191 mg/m³

Short-term exposure limit (15-minute reference period): 100 ppm | 384 mg/m³

Comments: Sk (Sk = Can be absorbed through skin.)

DNEL / PNEC

DNEL (toluene): 384 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

DNEL (toluene): 384 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (toluene): 192 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (toluene): 384 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (toluene): 226 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

DNEL (toluene): 226 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - Workers

According to EC-Regulation 1907/2006 (REACH)

DNEL (toluene): 56,5 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - General population

DNEL (toluene): 226 mg/kg bw/day
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - General population

DNEL (toluene): 8,13 mg/kg bw/day
Exposure: Oral
Duration of Exposure: Long term – Systemic effects - General population

PNEC (toluene): 0,68 mg/L
Exposure: Freshwater

PNEC (toluene): 0,68 mg/L
Exposure: Marine water

PNEC (toluene): 16,39 mg/L
Exposure: Freshwater sediment

PNEC (toluene): 2,89 mg/kg
Exposure: Soil

PNEC (toluene): 13,61 mg/L
Exposure: Sewage Treatment Plant

8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

General recommendations

Observe general occupational hygiene.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible collect spillage during work.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

If the ventilation at the work place is not sufficient, use a half or whole mask with an appropriate filter or an air-supplied respiratory protector. The choice depends on the concrete work situation and how long you will be using the product.

Skin protection

Special work clothing should be used. When working with this product for a long period of time, use a protective suit.

Hand protection

Use protective gloves. The concrete work situation is not known. Contact the suppliers of the gloves for help on the glove type. Please note that elastic gloves stretch when used. The thickness of the gloves, and therefore their penetration time, will be reduced. Moreover, the temperature of the glove in use is about 35°C, while the standard test, EN 374-3, is done at 23°C. The penetration time is therefore reduced by a

factor of 3.

Eye protection

Use safety glasses with a side shield.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm ³)
Liquid	Various colours	Aromatic	-	-	1

Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-95	110	-

Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
4	-	480
Explosion limits (Vol %)	Oxidizing properties	
1,3 - 8	-	

Solubility

Solubility in water	n-octanol/water coefficient	VOC
Insoluble	-	50 g/L (5 ww%)

9.2. Other information

Solubility in fat	Additional information
-	N/A

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity. Do not expose to heat (e.g. sunlight), because it can lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance	Species	Test	Route of exposure	Result
toluene	Rat	LD50	Oral	636 mg/kg
toluene	Rabbit	LD50	Dermal	> 5000 mg/kg
toluene	Rat	LC50	Inhalation	28,1 mg/L/4H

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

No data available.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs.

Aspiration hazard

May be fatal if swallowed and enters airways.

Long term effects

Reproductive toxicity: This product contains teratogenic substances which can do long-term damage to human offspring. The effects on the child can be: death, deformity, delayed development, and functional disorders. This product contains substances that can give chemical pneumonia if inhaled. The symptoms of chemical pneumonia can appear after several hours.

Reproductive toxicity: This product contains substances which can do damage to reproductive capacity, e.g. damage to germ cells or hormonal regulation. The effects can be: sterility, reduced fertility, menstruation disorders, etc.

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Species	Test	Test duration	Result
toluene	Daphnia	LC50	48h	3,8 mg/L
toluene	Fish	LC50	96h	5,5 mg/L
toluene	Algae	EC50	72 h	12,5 mg/L

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
No data available.			

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BFC
toluene	Yes	2,73	No data available

12.4. Mobility in soil

toluene : Log Koc= 2,240287, Calculated from LogPow (Moderate mobility potential.).

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

This product contains substances which can accumulate in the food chain because they are bioaccumulative substances. Bioaccumulative substances can accumulate in fat tissue and are not easily secreted.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

Waste

EWC code
20 01 28

Specific labelling

-

Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

SECTION 14: Transport information

This product is covered by the conventions on dangerous goods.

14.1 – 14.4

ADR/RID

14.1. UN number	1139
14.2. UN proper shipping name	COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining)
14.3. Transport hazard class(es)	3
14.4. Packing group	II
Notes	-
Tunnel restriction code	-

IMDG

UN-no.	1139
Proper Shipping Name	COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining)
Class	3
PG*	II
EmS	-
MP**	-
Hazardous constituent	-

IATA/ICAO

UN-no.	1139
Proper Shipping Name	COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining)
Class	3
PG*	II

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC. Pregnant and nursing women must not be exposed to the effects of this product. The risk, and possible technical precautions or design of the workplace to avoid such risk, must therefore be evaluated.

Demands for specific education

-

Additional information

Sources

COUNCIL DIRECTIVE 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

IDirective 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

EC Regulation 1272/2008 (CLP).

EC regulation 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225 - Highly flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

H361 - Suspected of damaging fertility or the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure.

The full text of identified uses as mentioned in section 1

-

Other symbols mentioned in section 2

-

Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by

kbb

Date of last essential change (First cipher in SDS version)

-

Date of last minor change (Last cipher in SDS version)

-